

SUNBLOCK



The windowfilm professionals!

Sunblock Copper 50

Total Solar Energy Rejected	62 %
Visible Light Transmittance	45 %
Visible Light Absorptance	32 %
Visible Light Reflectance	23 %
Solar Energy Absorptance	34 %
Solar Energy Reflectance	37 %
Solar Energy Transmittance	29 %
UV Rejected	> 98%
Thickness	50 µm
Color	Copper shade
Warranty	10 years

Percentages valid when applied to 4mm clear glass.

Internal use only	Clear Single Pane	Tinted Single Pane	Clear Double Pane	Tinted Double Pane
Installation recommendations	●	●	●	●

● can be installed without risk of glass breakage and/or double glazed unit seal failure ●● can be installed after risk-inspection ●●● not advisable to install, glass breakage and/or double glazed unit seal failure may occur
 ●●●● when installed, major risk for glass breakage and/or double glazed unit seal failure
 * These recommendations can be used solely as reference. Expert advice can be requested.

Features:

- Provides a 'warm' appearance
- Can reduce energy consumption of cooling systems.
- Improves working/living environment by cutting excessive solar heat gain.
- Reduces glare to ease eyestrain.
- Removes Ultra Violet radiation, reducing fading of fabrics, furnishings and interiors.
- Scratch resistant coating for long life and easy cleaning.
- Sputter Coated film

www.sunblock.nl

tel. 06 - 30 303 303