

SUNBLOCK



The windowfilm professionals!

Sunblock Clearview 20

Total Solar Energy Rejected	76 %
Visible Light Transmittance	22 %
Visible Light Absorptance	33 %
Visible Light Reflectance	45 %
Solar Energy Absorptance	37 %
Solar Energy Reflectance	48 %
Solar Energy Transmittance	15 %
UV Rejected	> 99%
Thickness	50 µm
Color	Natural
Warranty	10 years

Percentages valid when applied to 4mm clear glass.

Internal use only	Clear Single Pane	Tinted Single Pane	Clear Double Pane	Tinted Double Pane
Installation recommendations	●	●	●●	●●●

● can be installed without risk of glass breakage and/or double glazed unit seal failure ●● can be installed after risk-inspection ●●● not advisable to install, glass breakage and/or double glazed unit seal failure may occur
 ●●●● when installed, major risk for glass breakage and/or double glazed unit seal failure
 * These recommendations can be used solely as reference. Expert advice can be requested.

Features:

- Excellent heat gain reduction whilst maintaining a large amount of natural light.
- Can reduce energy consumption of cooling systems.
- Improves working/living environment by cutting excessive solar heat gain.
- Reduces glare to ease eyestrain.
- Removes Ultra Violet radiation, reducing fading of fabrics, furnishings and interiors.
- Excellent film for use in residential areas, natural color, hard to see through.
- Sputter Coated film

www.sunblock.nl

tel. 06 - 30 303 303